

### OCAL BLUE LARGE RADIUS ELBOWS

List Each

Type	12"	15"	18"	24"	30"	36"	42"	48"
LRELL1	54.97	59.98	70.89	89.70	104.39	123.57	150.30	156.77
LRELL11/4	56.22	71.30	79.18	97.61	114.81	135.53	154.02	185.29
LRELL11/2	64.35	75.24	89.03	110.01	130.68	153.20	183.45	209.62
LRELL2	80.54	104.08	111.91	142.08	168.35	197.49	237.98	250.22
LRELL21/2	118.17	141.06	167.04	213.82	239.36	281.89	339.26	353.56
LRELL3		175.71	206.41	258.44	299.97	352.98	424.43	446.39
LRELL31/2			270.57	302.32	379.58	418.20	525.74	584.34
LRELL4			290.18	348.47	402.02	471.03	605.43	635.88
LRELL5					674.19	722.61	880.49	922.93
LRELL6						964.09	1036.56	1073.42

Order example: LRELL1X12-G

### OCAL SEALTIGHT CONDUIT FITTINGS

Type	List Each 45°	List Each 90°	List Each Straight
ST1/2	44.37	43.98	37.67
ST3/4	52.48	51.99	42.45
ST1	74.67	78.83	50.89
ST11/4	137.92	144.12	81.03
ST11/2	151.22	152.86	95.90
ST2	197.85	208.86	167.62
ST21/2	605.93	611.14	531.72
ST3	713.54	732.48	584.22
ST4	983.40	1007.42	756.46



Order example: ST1/2-G, ST1/290-G, ST1/245-G

### OCAL GROUNDED SEALTIGHT FITTINGS

Type	List Each 45°	List Each 90°	List Each Straight
ST1/2G	77.69	88.61	67.54
ST3/4G	121.11	131.41	83.93
ST1G	155.20	157.21	101.89
ST11/4G	179.10	182.27	111.28
ST11/2G	221.26	230.90	157.90
ST2G	276.77	354.52	236.92
ST21/2G	959.95	1077.01	886.57
ST3G	1207.03	1518.60	983.86
ST4G	1359.47	1617.91	1141.57

Order example: ST1/2G-G, ST1/290G-G, ST1/245G-G