



| | |
|-----------------------|-------------------------|
| BURNDY Catalog Number | GAR3904BU |
| UPC Number | 781810001516 |
| Description | 4-4/0 CU 2.5-3.5IPS GRD |
| Status | Active |

Web Use
BURNDY Product Line

| Dimensional | |
|----------------------------------|---|
| Width (in) | 6 |
| Length (in) | 1.75 |
| Height (in) | 6.5 |
| Size (Hex) or Size (Bolt) | 3/8 |
| Size (Hex) or Size (Bolt) - in | 0.38 |
| B Length (in) | 1.75 |
| General | |
| Product Description | Mechanical Grounding Connector, Conductor to Water Pipe, 4-4/0 AWG, 2-1/2"-3-1/2" Pipe, 3/8" Stud |
| Other | |
| Type of U Bolt | 1033 |
| Approvals / Certifications | |
| UL Listed | Y |
| CSA Certified | Y |
| ROHS Compatible | Compliant |
| UL Recognized | N |
| CULUS | N |
| Industry Standards | UL467 |
| Rated for Direct Burial | Y |
| Conductor(s) | |
| Copper Tube Size (SCH40) - Range | 2 1/2-3 1/2 |
| Rod Size (Range) | N/A |
| Copper Solid Size (Range) | N/A |
| Copper Stranded (Range) | 4-4/0 |
| Rebar Size (Range) | N/A |
| Physical | |
| Type of Hardware | DURIUM® Silicon Bronze |
| Installation Torque | 200 |
| Type of Plating | Unplated |
| Plated (Yes or No) | N |
| Product Material | Copper Alloy |
| Documentation | |