



| | |
|-----------------------|-------------------------|
| BURNDY Catalog Number | K2A29U |
| UPC Number | 781810600108 |
| Description | TWO:6STR-250 DUAL RATED |
| Status | Active |

Web Use
BURNDY Product Line

| Dimensional | |
|----------------------------|---|
| Width (in) | 1.66 |
| Length (in) | 2.56 |
| Bolt Hole Size (in) | 0.38 |
| Thickness | 0.25 |
| D - in | 1.5 |
| Pad Width (in) | 1.66 |
| N (in) | 0.5 |
| General | |
| Number of Conductors | 2 |
| Number of Holes | 1 |
| Product Description | Aluminum Universal Terminal, 2 Conductor, 1 Hole, 6 AWG (Str)-250 kcmil, 3/8" Stud, 2 Screws, Al/Cu Rated, Tin Plated |
| Conductor(s) | |
| Aluminum Size (Range) | 6 AWG-250 kcmil |
| Copper Solid Size (Range) | N/A |
| Copper Stranded (Range) | 6 AWG-250 kcmil |
| Physical | |
| Installation Torque | 275 |
| Type of Plating | Unplated |
| Connector Type | Terminal |
| Bolt Hole Size | 3/8 |
| Plated (Yes or No) | N |
| Product Material | Aluminum |
| Approvals / Certifications | |
| Rated for Direct Burial | N |
| UL Listed | Y |
| CSA Certified | Y |
| ROHS Compatible | Non-Compliant |
| UL Recognized | N |
| CULUS | N |
| Industry Standards | UL468A-468B |