



Conduit Fittings-PVC Coated

T&B Catalog Number:

ST11/4-G

UPC Number:

70450840653

Status:

Active

Description:

1-1/4 in. Dark Gray PVC Coated Straight Liquidtight Connector. Fitting material-Steel.

Features

A minimum of .040 in. (40 mil) PVC coating is bonded to the exterior.

Double coated with a nominal .002 in. (2 mil) blue urethane on both the interior and exterior, before PVC coating is applied.

Pressure-sealing sleeves are designed to protect the connection.

PVC coated connectors are available in straight, 45 degree and 90 degree configurations

Ocal uses T&B Industrial Liquidtight fittings to insure quality installations.

Application

To positively bond conduit to box or enclosure

General

Custom_Finish	lt_114_s
Trade Size (inches)	1 1/4
Material	Steel
Finish	PVC Coated
Color	Dark Gray

Dimension Information

Pipe Size (Metric Size Designator*)	35
Dimension A (inches)	2 9/32
Dimension B (inches)	2 1/2
Dimension C (inches)	13/16

Technical Information

Chemical Resistance Chart	Available on Website
---------------------------	----------------------

Specifications

Ocal Specification Guide-1995 Master Format-PDF	Available on Website
Ocal Specification Guide-1995 Master Format-DOC	Available on Website
Ocal Specification Guide-2004 Master Format-PDF	Available on Website
Ocal Specification Guide-2004 Master Format-DOC	Available on Website

Packaging

Package in Units	20
T&B Sold in UOM	Each
T&B Weight Per UOM	0.77 lbs. Each

Application Support

Ocal PVC Coated Conduit System	Available on Website
--------------------------------	----------------------